



JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

☞ JIS C 3307 : 2000
(JCMA)

**600 V Polyvinyl chloride insulated
wires**

ICS 29.060.20

Descriptors : polyvinyl chloride, sheathed cables, sheathed conductors, rigid
conductors

Reference number : JIS C 3307 : 2000 (E)

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of International Trade and Industry through deliberations at the Japanese Industrial Standards Committee, as the result of proposal for revision of Japanese Industrial Standard submitted by the Japanese Electric Wire & Cable Maker's Association (JCMA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law. Consequently **JIS C 3307 : 1993** is replaced with this Standard.

Attention is drawn to the possibility that some parts of this Standard may conflict with a patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have technical properties. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying the patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have the said technical properties.

Date of Establishment: 1951-09-18

Date of Revision: 2000-12-20

Date of Public Notice in Official Gazette: 2000-12-20

Investigated by: Japanese Industrial Standards Committee
Divisional Council on Electricity

JIS C 3307:2000, First English edition published in 2001-11

Translated and published by: Japanese Standards Association
4-1-24, Akasaka, Minato-ku, Tokyo, 107-8440 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2001

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

600 V Polyvinyl chloride insulated wires

Introduction This Japanese Industrial Standard corresponds to IEC 60227-3 *Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V—Part 3 : Non-sheathed cables for fixed wiring* published as the second edition in 1997, but includes the technical deviations due to national reasons.

There is another Japanese Industrial Standard, JIS C 3662-3 : 1998 (Japanese language) *Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V—Part 3 : Non-sheathed cables for fixed wiring*, which is just translation of IEC 60227-3 : 1997 without technical deviations.

1 Scope This Standard specifies single core electric wires, insulated with compound mainly composed of polyvinyl chloride (hereafter referred to as “PVC”), to be used mainly in general electric installations and wiring of electric machinery and apparatus at 600 V or under (hereafter referred to as “wires”).

Remarks : The International Standard corresponding to this Standard is given below.

In addition, abbreviations which denote the degree of correspondence in the contents between the relevant International Standard and JIS are IDT (identical), MOD (modified) and NEQ (not equivalent) according to ISO/IEC Guide 21.

IEC 60227-3 : 1997 *Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V—Part 3 : Non-sheathed cables for fixed wiring* (NEQ)

2 Normative references The following standards contain provisions which, through reference in this Standard, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS C 3005 *Test methods for rubber or plastic insulated wires and cables*

JIS C 3101 *Hard-drawn copper wires for electrical purposes*

JIS C 3102 *Annealed copper wires for electrical purposes*

JIS C 3152 *Tin coated annealed copper wires*

3 Symbol The symbol for wires shall be “IV”.

4 Characteristics The characteristics shall be as shown in Table 1 when the tests are carried out in accordance with 6.