



JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS G 0580 : 2003

(JSSA/JSA)

**Method of electrochemical
potentiokinetic reactivation ratio
measurement for stainless steels**

ICS 77.060; 77.140.20

Reference number : **JIS G 0580 : 2003 (E)**

PROTECTED BY COPYRIGHT



Documents

Document Sharing Hub

55

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee, as the result of proposal for revision of Japanese Industrial Standard submitted by the Japan Stainless Steel Association (JSSA)/the Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14. Consequently **JIS G 0580 : 1986** is replaced with this Standard.

Date of Establishment: 1986-02-01

Date of Revision: 2003-03-20

Date of Public Notice in Official Gazette: 2003-03-20

Investigated by: Japanese Industrial Standards Committee
Standards Board
Technical Committee on Iron and Steel

JIS G 0580 : 2003, First English edition published in 2003-07

Translated and published by: Japanese Standards Association
4-1-24, Akasaka, Minato-ku, Tokyo, 107-8440 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

PROTECTED BY COPYRIGHT

Contents

	Page
1 Scope	1
2 Normative references	1
3 Measuring apparatus	1
4 Test solution	2
5 Test piece	2
6 Measuring method	3
7 Reactivation ratio (R)	4