

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

Ⓔ JIS K 6329 : 1997

Retreaded tires

ICS 83. 160. 01

Descriptors : tyres, vehicle components, pneumatic tyres, waste recovery

Reference number : JIS K 6329 : 1997 (E)

K 6329 : 1997

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of International Trade and Industry through deliberations at Japanese Industrial Standards Committee in accordance with the Industrial Standardization Law:

Date of Establishment: 1954-05-22

Date of Revision: 1997-03-20

Date of Public Notice in Official Gazette: 1997-03-21

Investigated by: Japanese Industrial Standards Committee

Divisional Council on High-Molecular
Materials

JIS K 6329:1997, First English edition published in 1997-07

Translated and published by: Japanese Standards Association
4-1-24, Akasaka, Minato-ku, Tokyo, 107 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

Retreaded tires

1 Scope This Japanese Industrial Standard specifies functionally restored rubber tires (hereafter referred to as “retreaded tires”) which have been regenerated to be usable by retreading tread rubber on the worn tires, for automobiles, industrial vehicles, construction vehicles and agricultural machines.

Remarks 1 The standards cited in this Standard are as follows:

JIS B 9202 *Dimension and load ratings of tires for agricultural machines and implements*

JIS B 9205 *Tires for agricultural implements and machineries*

JIS D 4201 *Designation system of tyre, tube, rim band, and flap for automobiles*

JIS D 4202 *Automobile tyres — Designation and dimensions*

JIS D 4230 *Tires for automobiles*

JIS D 6401 *Dimensions and load ratings of tires for industrial vehicles and off the road service*

JIS D 6403 *Tires for industrial vehicles*

JIS K 6200 *Glossary of terms used in rubber industry*

JIS K 6251 *Tensile testing methods for vulcanized rubber*

JIS K 6256 *Adhesion testing methods for vulcanized rubber*

JIS K 6370 *Compounded rubber for retread and repair*

2 The units and numerical values in { } in this Standard are based on the traditional units and are appended for informative reference.

2 Definitions The definitions of main terms used in this Standard follow JIS B 9202, JIS B 9205, JIS D 4202, JIS D 4230, JIS D 6401, JIS D 6403 and JIS K 6200.

3 Classification Retreaded tires are classified as follows:

- (1) **Retreaded tire for automobiles** Follow JIS D 4202 or the standard established by public institution.
- (2) **Retreaded tire for industrial vehicles or construction vehicles** Follow JIS D 6401 or the standard established by public institution.
- (3) **Retreaded tire for agricultural machines** Follow JIS B 9202 or the standard established by public institution.

4 Dimensions The dimensions (limited to the maximum value of total width and outside diameter) of retreaded tire shall be as follows. In this case, the standard established by public institution may be applied.